



GREENCROP

www.greencrop.co.uk

DB Dribble Bar Applicators



DB1240UMB

The DB range of Dribble Bars are simple, heavy-duty, low-cost dribble bar band applicators that have been designed with the user in mind.

It is available in two formats: UMB - for umbilical use
 TNK - for mounting on a tanker (6020 and 7224 only)

Standard features include:

- **Standard CAT II three point link mounting** - UMB model only
- **Standard CAT II 4 point link mounting** - TNK model only
- **Fully galvanised construction** - protects machines against corrosion
- **Fully hydraulic folding**
- **Flexible outlet pipes** - discharge hoses “comb” their way through the crop
- **Hydraulic driven Vogelsang ExaCut Distributor/Macerator unit**
- **Double acting hydraulic operated - 150mm (6”) inlet valve** - UMB model only
- **Heavy duty swing arm c/w hose moving shoe** - UMB model only

www.greencrop.co.uk

Model	Working width (m)	Outlets (mm)
DB6020TNK	6	20 x 50
DB6020UMB	6	20 x 50
DB7224TNK	7.2	24 x 50
DB7224UMB	7.2	24 x 50
DB9030UMB	9	30 x 40
DB1240UMB	12	40 x 40

OPTIONS

Code	Model
DB-TNKLNK	Simple N2 4 point link system c/w weld on lugs for welding on to tanker
	Factory fit onto existing tanker
03-620-102	102mm (4") swivel on umbilical feed coupling
	Shut off taps (to close down application width or for shutting off tramline outlets)
	Pneumatic outlet shutoff system
HER-LAU-DAH	Hertell 150mm (6") hydraulic DA valve to drain macerator stone trap



Dereham Road, Beeston, King's Lynn, Norfolk PE32 2LE
 Tel 01328 701992
 Fax 01328 700111
 Email enquiries@greencrop.co.uk
www.greencrop.co.uk

Dealer stamp