



MINI VERSION 015







c
В

RANGE	A mm	B mm	C mm	Power Consumption kw	Weight kg
SEPCOM® 015	650	1.200	1.800	2.2	120
SEPCOM® 045	975	1.950	2.767	4	480
SEPCOM® 065	975	2.250	2.767	5.5	570

- · Stainless steel casing
- · Screw manufactured from self-cleaning SINT engineering polymer.
- Stainless steel screen
- working conditions and maintenance of the machine

* Capacity may vary depending on the type of input material,



GREENCROP IRRIGATION

Dereham Road, Beeston, King's Lynn PE32 2LE Tel: 01328 701992 Fax: 01328 700111 Mob: 07881 787997 Email: howard@greencrop.co.uk www.greencrop.co.uk



SEPCOM® Solids-Liquid Separator







WAMGROUP

MULTIPLE PATENTS PENDING

Biogas Digestate Cattle Manure













www.greencrop.co.uk





Specially formulated for animal manure and digestate matter from biodigestors, SEPCOM® is simple, reliable, efficient and economical.

Re-using slurry offers enormous advantages in terms of transportation, storage, cleanliness and energy saving.

Separating solids from the liquid in the slurry is THE ANSWER TO THE URGENT ISSUE OF NITRATES AND PHOSPHATES ENTERING THE GROUNDWATER.



LIQUID PHASE

- Easy to spread, mix and pump
- Minimum residual sedimentation or incrustation
- Can be used for washing out sheds and pens
- Excellent for fertigation
- · Reduced odour
- Reduced space requirement for slurry tanks



Flushin



SOLID PHASE

- Odourless
- Can be shoveled, easy to store and convey
- Can be used as bedding for cattle
- Organic fertilizer
- Product can be marketed
- Self-composting product



Can be shoveled, easy to transport and store even in enclosed spaces



Ideal cattle beddir



Product can be marketed







