

## **Submersible Dirty Water Packs**



## www.greencrop.co.uk

Packaged dirty water pumping systems for short distance application of dirty water and yard run off.

Packs comprise the following:

- Heavy-duty submersible grinder pump, complete with inlet macerator, and high-pressure vortex impeller.
- Pump control panel complete with float switch, isolator, pump protection overload, hour meter, and connection for 24v alarm circuit.
- Flexible pump connection hose with quick release coupling.
- 200m x 2" PE pipe in 100m lengths, complete with couplings.
- 1 x AKT155 sprinkler complete with galvanised sledge and quick release coupling.



Single phase systems using a 1.5kw 240v single phase pump will give a nominal output of  $4m^3$  per hour, over an area of  $1017m^2$ , giving an application of 3.3mm per hour.

Three phase systems using a 3.7kw 415v three phase pump will give a nominal output of 6m<sup>3</sup> per hour, over an area of 1194m2, giving an application of 4.3mm per hour

Three phase systems are extendable to 300m, subject to restrictions caused by static head.



Dereham Road, Beeston, King's Lynn, Norfolk PE32 2LE Tel 01328 701992 Fax 01328 700111 Email <u>enquiries@greencrop.co.uk</u> www.greencrop.co.uk Dealer stamp