



GREENCROP IRRIGATION

High Quality Vacuum Tankers



Range	Capacity gals/ litres	Pump	Wheels	Width mm	Length mm	Weight
GCTX1500S	1495 / 6650	8000 ltrs	560/60x22.5	2550	6020	2590
GCTX2000S	1985 / 9010	8000 ltrs	560/60x22.5	2650	6350	3180
GCTX2200CS	*2050 / 9225	11000 ltrs	28.1x26	2700	6690	3350
GCTX3000T	2920 / 13250	11000 ltrs	560/60x22.5	2550	7690	4200

*cut in barrel drop axle and mudguards

www.greencrop.co.uk



General specifications include:

High quality paint finish
 Coil spring drawbar with swivel eye hitch
 Full barrel length chassis
 Battioni pump with remote handle
 Hydraulic brakes and hand brake
 Fully wired light system
 PTO shaft
 Galvanized quick fit couplings
 Hydraulic valve for emptying
 Manual valve for filling
 Side port at front near side with 2" tap
 15ft x 6" of reinforced suction hose



Greencrop Tankers are quality British Manufactured. The tanker barrels are rolled from high quality 6mm and 8mm steel plate.

All tankers incorporate a full length chassis for added strength and are ideal for mounting dribble bars, slitters and injectors.

Single axle tankers, 1500 gallon and above are fitted with a sprung drawbar and swivel hitch as standard.



All steel used is to EN.BS.10025 standard and operates B.S.5750 part 2 (ISO 9002) quality assurance system.

High quality vacuum pumps with remote manual operation or optional hydraulic changeover. PTO or hydraulic drive. Sprung drawbar are fitted to larger tankers to eliminate shock loads, therefore reducing stress on the operator and wear on both tractor and tanker. Swivel hitches are fitted to the tankers to reduce wear on both tractor hook and the tanker eye, it also eliminates the risk of combined rollover i.e. the tanker is independent from the tractor.

Full length chassis, side fill point with 2" wash down tap, wide choice of wheels. Spare oil carrier and twin pressure and suction protection valves.

The dish ends are overlapped inside the barrel (not but welded) to give extra strength.

Full road lights and braking system. Quick release couplings are fitted as standard to all manual valves for quick clean and easy attachment of the suction hose. Low level splash spreader plate.



GREENCROP IRRIGATION

Dereham Road, Beeston, King's Lynn, Norfolk PE32 2LE
 Tel 01328 701992
 Fax 01328 700111
 Email enquiries@greencrop.co.uk
www.greencrop.co.uk

Dealer stamp